

# Oscillating Abrasion Tester 6100



Surface Abrasion / Erosion Testing

## Measure resistance to surface abrasion and scratching.

The Oscillating Abrasion Tester generates surface damage reflective of what is commonly seen in real life. Test specimens are subjected to an abrasive media that shifts significantly within the tray resulting in scratches, pits and surface roughening on the specimen surface.

## Drive system provides consistent results.

A scotch-yoke drive system allows an even distribution of movement centered on the tray. This ensures the pressure of the abradant is consistent for the duration of the test. Test parameters can be changed with an adjustable stroke length and variable speed.

## Detachable tray offers testing versatility.

With the specimen holder integrated in a detachable tray, the standard test arrangement is intended for flat specimens up to 1/2 inch thickness. Customized holders can be developed to evaluate non-standard shapes. An optional test kit is also available to conduct the "Bayer Test" for contoured lenses. Additionally, using abrasive slurry allows for small-scale, controllable tests to assess material erosion resistance.



# Oscillating Abrasion Tester 6100

Surface Abrasion / Erosion Testing

## Standard Features:

Stroke lengths of 1.0", 2.0", 3.0", 4.0"  
Variable stroke speed from 100 – 200 cycles per minute  
Add 100 stroke selector switch  
Stainless steel specimen tray (9 1/2" x 12" x 2 1/2" deep)  
Vibration isolator mounts  
115V/230V switchable



## Optional Accessories (sold separately):

Alundum ZF-12 abrasive media  
Stainless steel specimen tray (9 1/2" x 12" x 4" deep)  
Specimen tray cover  
Bayer test kit

## Oscillating Abrasion Tester Includes:

Specimen Tray with Integrated Holder  
Specimen Spacers (set of 8)  
4/10 Silica Abrasive Media (50 lb.)  
6" Rule  
Spirit Bubble Level  
Specimen Removal Tool  
Disposable Specimen Tray Cover



*Send us your materials for  
a product demonstration*



Setting the Industry Standard

455 Bryant Street  
North Tonawanda, New York 14120 USA

For more information:  
Call 1.800.333.5300 (U.S.) or 716.694.4000 (outside U.S.)  
Fax 716.694.1450  
Email us at [sales@taberindustries.com](mailto:sales@taberindustries.com)  
Visit us at [www.taberindustries.com](http://www.taberindustries.com)